
# INNOVATION THROUGH DESIGN

# **EZI-RETAIN**GALVANISED STEEL RETAINING WALL POSTS



## 7STEEL EZI-RETAIN™

### STEP 1

Setout your wall, mark your post positions depending on the length of your timber sleepers.

Determine which sections of EZI-RETAIN posts you need (see over page).

Cement your posts into the ground at the correct height and you are ready to finish your wall.

### STEP 2

Drop in your timber sleepers (200x75mm are recommended), ensure first sleeper is embedded 100mm into the ground).

Nail down your capping timber (optional),150x50 beveled edge is recommended but choose your own style. Prior to back filling, suitable drainage is recommended eg. ag pipe and blue metal to avoid moisture build up.

### STEP 3

Back fill up to your EZI-RETAIN wall and your garden has a stylish brand new look.

Add a set of EZI-STAIR galvanized stair stringers and your new area is now also easily accessible.

Easy to use for the landscape or DIY gardener! EZI-RETAIN makes a big job easy!!!!



FOR INFORMATION ABOUT OUR PRODUCTS AND SERVICES PLEASE VISIT OUR WEBSITE

# EZI-RETAIN™/ GALVANISED STEEL RETAINING WALL POSTS

# GREAT LOOK, EASY TO USE

EZI-RETAIN posts are hot dip galvanized to provide long life and a smart professional finish. All galvanizing meets AS/NZ 4680:2006.

Selecting and installing the EZI-RETAIN is easy. The system is designed for use with materials easily sourced from your local hardware or landscape supplier.

The EZI-RETAIN posts are designed to be used with 75mm sleepers, although 50mm sleepers can be used if required.

Determine the height of your wall and choose the correct size sections from the stock chart below. 7 Steel recommends that EZI-RETAIN posts be embedded half in the ground and concreted in place. Therefore for a 1000mm high wall you will require a 2100mm EZI-RETAIN POST, this will take 5x200x75 sleepers (the first sleeper should be embedded 100mm into the ground).

7 Steel recommends that you check with your local council before installation to ensure local government compliance, consultation with a engineer is also recommended where large quantities of earth are being retained.

# **EZI-RETAIN SECTIONS & SIZES**

	900mm	1200mm	1500mm	1800mm	2100mm
EZI RETAIN H SECTIONS	1	1	1	1	1
EZI RETAIN C SECTIONS	1	1	1	1	1

CODE IMAGE DESCRIPTION

ERH

**H section:** use to join sleepers in a straight line. **Size:** 100x55mm

C section: use to make 0-90° turns in wall (2 ERCs required) or for end of wall.

Size: 100x50mm



# ENQUIRIES AND SALES

NSW - SYDNEY 142 Magowar Road Girraween NSW 2145 Ph: 02 8071 4383 Fax: 02 9896 5968 Enquiries: 1-800-7-STEEL (78335) E-mail: sales@7steel.com.au

VICTORIA - MELBOURNE 46 Chelmsford Street, Williamstown VIC 3016 Ph: 03 9397 2451 Fax: 03 9397 2880 Mobile: 0419 575 398

E-mail: shaiwalker@7steel.com.au

QUEENSLAND - GYMPIE 7-9 Woodbine Street Gympie QLD 4570 Ph: 07 5482 5322 Fax: 07 5482 7072 Mobile: 0488 489 830

Enquiries: 1-800-7-STEEL (78335) E-mail: sales@7steel.com.au QUEENSLAND - MACKAY 31 Evans Avenue North Mackay QLD 4740 Mobile: 0409 501 175 Fax: 07 4957 2115

Enquiries: 1-800-7-STEEL (78335) E-mail: tonysmith@7steel.com.au

